

FEATURES

Timber and stainless steel construction
 Back to back or single sided application
 Concealed fixing
 Standard timber: 32mm or 40mm diam. solid Oak (stains avail. as special finish)
 Standard timber finishes: clear lacquer
 Standard stanchion finishes: satin [S], Electroplating available soon, please call office to discuss [EP].
 Special stanchion finishes: polished [P], powder coating [PC]

BCA COMPLIANT

A1428.1

TYPE A 25 Diam



TYPE B 50x25



TYPE C 25x25



TYPE D 25x25 Offset



OPTIONS: 60c/l in from each end

STANCHION FINISHES: SATIN [S], ELECTROPLATING [EP], POLISHED [P], POWDER COATING [PC]



40 diam arcadia rail with
TYPE A stanchion



40 diam arcadia rail with
TYPE B stanchion



40 diam arcadia rail with
TYPE C stanchion



40 diam arcadia rail with
TYPE D stanchion

INDEX+Co can manufacture custom lengths upon request starting from 600mm up to 2400mm

TO SPECIFY PLEASE USE THE FOLLOWING GUIDE:

1. Length (mm)
2. Arc T
3. 45
4. V=vertical H=horizontal
5. Type of stanchion
6. Spacing from each end (ie. 60 or 160)
7. FINISH:
 - CL = Clear
 - ST = Stain
8. GLOSS LEVEL:
 - M = Matte
 - S = Satin
 - P = Polished (gloss)

SPEC EXAMPLE:

Arcadia Timber Rail 2000mm
 45mm diam., vertical, 50x25mm
 end fixings, Type B satin s/steel
 stanchions 160mm (c/l) in
 from each end, clear, matte

SPEC EXAMPLE CODE:

2000ARCT45/V/B/S/160/CL/M

ALL MEASUREMENTS IN MILLIMETRES